

DESCRIPTION

CEMENT REMOVER SUPER is a strong blend of powerful acids, special corrosion inhibitors, wetting agents, and surface tension reducing agents, specifically formulated to remove any residues or stains of cement or cement clinkers on metal surfaces and articles.

It causes no harm to coatings and it meets the criteria for not being harmful to the marine environment according to MARPOL Annex V. It can be applied safely on any metal surface and parts except for aluminum, zinc, tin, and its alloys.

APPLICATION & USE

CEMENT REMOVER SUPER is used to remove the cement or cement clinker residues from the cargo holds, deck, and surrounding loading area.

Prior to the application, sweep away the remaining cargo deposits using brushes, scrappers, compressed air, etc., but avoid using water (neither sea nor fresh water) for pre-washing the surfaces.

Prepare 1-2 samples (70:30, 50:50) with CEMENT REMOVER SUPER and fresh water to perform small tests and determine the suitable dilution. **Always add acid to water dilution. Never add water to acid.** Apply the product starting from the lower levels gradually to the upper ones.

Make sure that the applied chemical is left to react for 10-20 minutes before rinsing, depending on the environment conditions (temperature – humidity). Rinse the detergent before allowing to dry, using water under high pressure.

To enhance the effectiveness of the product, it is highly recommended to use fresh water. Fresh water should also be used for the final rinsing to remove the salt remains from the seawater. Persisting residues may require to repeat the above procedure or to perform spot cleaning with undiluted

product (directly). Avoid pumping the rinsing waters from the cargo holds with built-in bilge pumps of the vessel. You could use the portable ELECTRIC SUBMERSIBLE PUMP KIT instead.

TYPICAL PHYSICAL PROPERTIES

Appearance:	Liquid
Odor:	Pungent
Flash Point:	None
pH (neat):	< 1
Density at 20°C:	1.15 ± 0.05 kg/cm ³

NOTE: Always wear the appropriate personal protective equipment when using this product.

PACKAGING

CEMENT REMOVER SUPER is available 210 liter drums (PCN 9877012).

IMPORTANT INFORMATION

Drew Marine maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees.

Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.

FEATURES

- Concentrated formula
- Contains powerful acids, surfactants, and corrosion inhibitors
- Water soluble
- Non-flammable

BENEFITS

- Long shelf life
- Cost effective
- Easy to apply



Contact your Drew Marine representative for more information



Drew Marine.

400 Captain Neville Dr.
Waterbury, CT 06705 USA
1-973-526-5700
Drew-Marine.com

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.