

TANK SUPER CLEANER



DESCRIPTION

TANK SUPER CLEANER is a heavy duty, highly concentrated tank cleaner with strong emulsifying action, low odor, low toxicity, and biodegradability.

APPLICATION & USE

TANK SUPER CLEANER has a wide range of applications. It is suitable for cleaning double bottom, deep tank, cargo tanks, and bilges or generally fuel oil storage tanks. It may also be used for engine room and/or deck cleaning and degreasing, oil & organic deposits cleaning, fuel oils/heavy crude oils cleaning, organic contamination oil, gas freeing of deep tanks and fuel oil tanks.

It is highly recommended to pre-clean tanks using high pressure warm water since large deposits of oil or other residues in the tank must be removed to ensure an effective cleaning operation.

TANK SUPER CLEANER can be applied using all conventional mechanical or manual means, The amount and nature of contamination, the available heating facilities, the degree of cleaning required and the capacity of tanks to be cleaned must be taken into consideration when determining which dosage rate to use.

Best results are achieved in temperatures between 60°C to 80°C.

Recirculation Method

It is recommended that TANK SUPER CLEANER is mixed with water at a ratio between 2.0% and 6.0% i.e 20-60 litres per ton wash water.

Care should be taken, as under extreme conditions, the concentration should be considerably increased. Cleaning results are best when hot water is used (between 60°C to 80°C).

The procedure is the same as the direct injection method except that the tanks being washed are stripped back to the recirculation tank.

Care should be taken to observe when the solution becomes saturated.

Spot Cleaning

TANK SUPER CLEANER can be sprayed neat onto tank surfaces to be cleaned. Optimal results are achieved when hot water (between 60°C to 80°C) is used and when contact time is at least 30 minutes.

Spraying Method

Spray undiluted TANK SUPER CLEANER directly on the contaminated areas. Wait 15-30 minutes for the chemical to penetrate properly and rinse off with water.

PHYSICAL PROPERTIES

Appearance:	Pale, yellow liquid
Odor:	Hydrocarbon odor
Flash Point (PMCC):	> 61°C
Density at 20°C:	0.8 kg/cm ³

NOTE: Always wear the appropriate personal protective equipment when using this product.

PACKAGING

TANK SUPER CLEANER is available in 210LT drums (PCN 110102).

FEATURES

- Multipurpose emulsifier
- Ideal for fuel tank cleaning and gas-freeing
- Effective for cleaning and degreasing of bilge spaces and engine rooms
- Can be easily rinsed off, without any traces

BENEFITS

- Safe on most metal surfaces
- Does not affect coatings
- Easy to use by all conventional means
- Comparising biodegradable surfactants



Contact your Drew Marine representative for more information

IMPORTANT INFORMATION

Drew Marine maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees.

Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.



Drew Marine

400 Captain Neville Dr.
Waterbury, CT 06705 USA
1-973-526-5700
Drew-Marine.com

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.