

DESCRIPTION

The DREW GMXA Metering Systems accurately dose with minimal manual operation. The operation is based on an external control parameter or timed sequences, which can be planned up to seven days in advance. The system is designed for metering select marine chemical treatment products to pressures of up to 16 bar. It utilizes a microprocessor-controlled, solenoid-driven diaphragm metering pumps. The metering pump's integrated, sensor-free pressure measurement system auto compensates programmed feed rates during backpressure fluctuations. This feature immediately and optimally matches the output to the pressure conditions and properties of the liquid medium while protecting the pump and piping systems from overload situations.

Each system consists of a tank and steel frame that enables safe mounting to a metal deck, a pump mounted on the tank, and a fitting kit necessary for suction and discharge. A sensor is provided to alert the user of low chemical levels. Additional electrical connections are provided on the pump to allow for integration into the vessel's existing boiler or engine room control and alarm panel.

The pump selected is dependent on the marine application. Recommendations listed below are based on chemical compatibility and the pressures and flow rates required for treating typical shipboard systems. The DREW GMXA Metering System automatically sets optimal speed and stroke based on the flowrate settings. For specific applications not listed or for more information, contact your local Drew Marine representative.

APPLICATIONS

GMXA Metering System 1604: Cooling Water Treatment

- AMERSPERSE® 280 seawater cooling treatment.
- DREWSPERSE® SWD seawater dispersant

GMXA Metering System 1604 or 0424: Boiler Water, Fuel Oil, and Additional Cooling Water Treatments

Contact your local Drew Marine representative for more information and specific applications.



GMXA Metering System

SPECIFICATIONS

Operating Temperature: -10°C to 45°C (14°F to 113°F) Degree of
Protection: IP65

Power Supply: 100-230 VAC/50-60 Hz, 25/30W
Tank Capacity: 60 liters (15.85 gallons)
Tubing: 10 meters (32.8 feet),
flexible ½" PE

PUMP CAPACITY

Model	Maximum Pressure	Flow Rate	PCN
GMXA 1604	16 Bar	3.6L/h	1AB5496
PVT	(232 psig)	(0.95 gph)	
GMXA 0424	04 Bar	24L/h	1AB5497
PVT	(58 psig)	(6.34 gph)	

Flow rates will vary slightly depending on the pressure at the injection point. Higher viscosity fluids will reduce capacity. Higher specific gravity fluids will reduce suction lift. Positive suction recommended.



Contact your Drew Marine representative for more information

ORDERING INFORMATION

Product	PCN
GMXA Metering System 1604 PVT	1AB5494
GMXA Metering System 0424 PVT	1AB5495
Spare Pumps/Kits	
Pump, GMXA 1604	1AB5496
Pump, GMXA 0424	1AB5497
Spares Kit, GMXA 1604 PVT	1AB5498
Spares Kit, GMXA 0424 PVT	1AB5499



Contact your Drew Marine representative for more information

Drew Marine maintains Safety Data Sheets on all of its products. These documents contain health and safety information for the development of appropriate product handling procedures to protect your employees. Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.



Drew Marine®

**100 South Jefferson Road
Whippany, NJ 07981 USA
1-973-526-5700
Drew-Marine.com**

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.