AMERINE™ 2500



DESCRIPTION

Drew Marine compression packings are designed to minimize wear and damage to pumps and valves, thus reducing costs for maintenance and replacement. Because they are constructed for maximum packing life, inventory lasts longer and outlays for packing materials are also reduced.

APPLICATIONS

Commonly used for water service and ideal for general use. Also well suited for acids, moderate alkalis, most gases, petroleum and synthetic oils, and aromatic and aliphatic solvents.

EQUIPMENT

Centrifugal, rotary and reciprocating pumps, and valve stems.

MAXIMUM TEMPERATURE

To 260 °C

PH RANGE

0-12.0

MAXIMUM SHAFT SPEED

Maximum Shaft Speed is 11.3 m/s (2250 fpm)

MAXIMUM PRESSURE

35 bar (500 psi) rotary/centrifugal

CONSTRUCTION

- Special syntex fiber with each strand impregnated with PTFE dispersion both prior to and after braiding. Finished packing also has a break-in lubricant.
- This braided packing can be used for general service applications.
- Good chemical resistance.
- AMERLOCK® braid.

PERFORMANCE

- Non-abrasive and naturally resilient
- Excellent chemical resistance
- · Ensures an even sealing load
- Provides high tensile strength and good durability

SEALING PRODUCTS (AVAILABLE UPON REQUEST)

HIGH-GRADE COMPRESSION PACKINGS

AMERPACK® 2400 Packing

AMERFLON® 2001 Packing

AMERINE™ 1400 Packing

AMERFLON SG Stern Gland Packing Tank Lid Packing

AMERGRAF® 1000 Graphite Ribbon Packing

SPECIAL JOINTINGS AND ENGINEERED GASKETS

Special Sheet Jointing

- · Non-standard sizes and thicknesses.
- Special materials, including: Teflon® (virgin and glassfilled), vegetable fiber, Viton®, flexible graphite, graphite, red rubber.

Cut Flange Gaskets

- · Pre-cut to specifications for maximum convenience.
- Available materials include: Teflon (virgin and glass-filled) vegetable fiber, Viton, flexible graphite, rubber sheet.

Spiral Wound Gaskets

- Filler materials available for ANSI-standard pipe sizes include: flexible graphite, PTFE, mica graphite, ceramic.
- · Metal clad and heat exchanger gaskets.
- Boiler handhole gasket.



PACKAGING

SIZES:

Inches	mm
1/8"*	3.0
3/16"*	5.0
1/4"	6.0
5/16"	8.0
3/8"	9.52
7/16"	11.0
1/2"	12.7
9/16"	14.0
5/8"	16.0
3/4"	19.0
7/8"	22.0
1"	25.0

BOX SIZE: (APPROX.)

lbs.	Meters	PCN
1	24.3	8127103
1	14.8	8127145
2	14.8	8127178
2	11.2	8127202
2	7.2	8127236
2	5.4	8127269
5	10.5	8127293
5	8.7	8127335
5	7.0	8127368
5	5.0	8127426
10	7.3	8127442
10.5	6.1	8127483



400 Captain Neville Drive Waterbury, CT 06705 USA 1-973-526-5700 Drew-Marine.com

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.