

DESCRIPTION

SLCC-A condensate corrosion inhibitor is a liquid alkaline amine used to control corrosion in condensate return lines and on steam condensing surfaces by traveling and condensing with the steam. SLCC-A inhibitor neutralizes the corrosive effects of carbonic acid formed by carbon dioxide and maintains non-corrosive pH conditions from the point of condensation onward throughout the system.

SLCC-A corrosion inhibitor is used in our standard boiler water treatment programs for low-pressure boiler systems (0-32 bar) and medium-pressure steam propulsion vessels (32-60 bar). It is also used in our ULTRAMARINESM boiler water treatment program for high-pressure steam generating systems (60-84 bar).

SLCC-A condensate corrosion inhibitor is NSF registered as a nonfood compound under category G6, a water treatment product used in boiler steam lines for food contact in food processing establishments. It is also registered under category G7, a water treatment product used in boiler steam line for nonfood contact in food processing establishments.



Nonfood Compounds
G6, G7

APPLICATION & USE

Dosage, Testing, and Control

Continuously dose SLCC-A condensate corrosion inhibitor to maintain condensate pH within the specified range. Slug dosing may result in erratic pH conditions and/or triggering of false condensate salinity alarm.

The daily condensate pH test result determines the necessary dosage. For details on the testing procedure, refer to the appropriate control and dosage chart, or contact your local Drew Marine representative.

Feed Points

For low-pressure boiler systems, continuously dose SLCC-A corrosion inhibitor with diluted AMERZINE[®] corrosion inhibitor or diluted DREWPLEX[®] OX corrosion inhibitor using a common DREW[™] Beta Metering System to the feedwater line downstream of the feedwater recirculation offtake. If there is no feedwater recirculation, dose continuously to the feed pump suction.

For medium- and high-pressure boiler systems, continuously dose diluted SLCC-A corrosion inhibitor with diluted AMERZINE corrosion inhibitor or diluted DREWPLEX OX corrosion inhibitor using a common DREW Beta Metering System to the deaerator storage section or suction side of the feed pump.

TYPICAL PROPERTIES

Appearance:	Slightly hazy liquid
pH:	11.4
Specific Gravity @ 25°C:	1.0
Odor:	Slightly ammoniacal

NOTE: Always wear the appropriate personal protective equipment when using this product.

PACKAGING

SLCC-A condensate corrosion inhibitor is available in 25-liter containers (PCN 0011403).

IMPORTANT INFORMATION

Drew Marine maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees.

Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.



Contact your Drew Marine representative for more information



Drew Marine[®]

333 Church Street
Naugatuck, CT 06770 USA
1-973-526-5700
Drew-Marine.com

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.